

TOLL ROAD SIGNAGE

RESTRICTIONS

(a) Berm Signs

(1) Lighting reflectors on ground signs may project beyond the face of the sign. 4 February 1998 16 (2) Every ground sign shall provide rigid construction to withstand wind action in all directions.

(b) Wall Signs

(1) The surface face of all sign bulletins must be of sheet metal, wood or plastic, but the ornamental molding surrounding the face may be of wood construction.

(c) Marquee Signs

Marquee signs may be attached to or hung from a marquee. The lowest point of a sign hung from a marquee shall be at least eight (8) feet above the sidewalk or ground level, and further, such signs shall not extend or project beyond the corners of the marquee. Marquee signs may be attached to the sides and front of a marquee, and a sign may extend the entire length and width of said marquee, provided no sign shall extend more than six (6) feet above nor one (1) foot below such marquee, nor have a vertical dimension greater than eight (8) feet.

(d) Signs of V-Type or Back-to-Back Construction

(1) The angle between the faces of V-type signs shall be no greater than forty-five degrees (45°) measured back-to-back and the maximum distance at the nearest point between the two backs, as measured at the apex, shall not exceed one and one-half (1 1/2) feet.

(2) Back-to-back signs must be on common supports and the nearest point between the two backs shall not exceed one (1) foot plus the diameter of the intervening upright or support.